

InvisiGARD Paint Protection

Product No.: IPP-7510

Description: InvisiGARD Paint Protection is a 6 mil (150 micron) non-yellowing

urethane film coated with an aggressive removable acrylic adhesive system. This adhesive system is designed to remove without adhesive

transfer and/or damage to the applied surface.

Applications: Protection of automotive paint against chipping due to stone and

pebbles, bug and environmental damage, and abrasion. Due to the clarity and high gloss finish of this product, InvisiGARD does not alter

the aesthetics of the applied surface.

TECHNICAL DATA

Polycoated bleached kraft

	TECHNICAL DATA	
	IMPERIAL	METRIC
Adhesive thickness: Substrate Thickness:	2.0 mils (0.0020") 6.0 mils (0.0060")	0.0508 mm 0.1524 mm
Peel Adhesion (PSTC-1):	25.0 oz/inch	16.3 N/2.5 cm
Shear Adhesion (PSTC-7):	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile (PSTC-31):	54 lbs/inch width	244 N/2.5 cm
Elongation:	410%	410%
Maximum continuous use Temperature:	212°F	100°C
Minimum application Temperature:	-10°F	-23°C
Release Liner:	90 lbs/ream	148 GSM

The information listed is in good faith and has been established from sources believed to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.

Copyright © 2004 [Auto Trim DESIGN]. All rights reserved.

InvisiGARD is a registered trademark of Auto Trim DESIGN of Northeast Wisconsin, Inc.

Auto Trim DESIGN of Northeast Wisconsin, Inc.

1694 Silverspring Drive Appleton, WI 54913-5441 (920) 832-0094 FAX(920) 832-0098 www.autotrimdesign.com